

755 Awning Window

Features:

- Beautiful, true brick mould exterior frame perimeter
- Low profile handle folds in and provides a popular aesthetic appeal
- Narrow profile permits expanded viewing area
- Insulated glass panels with optimum thermal air space featuring warm-edge spacer system
- Concealed hinges and hardware let you open casement windows 30 degrees for better ventilation and easier cleaning
- Full screens mount on the interior and are removable for easy cleaning
- Charcoal fiberglass mesh screen
- Jamb depth: 3.25"
- Limited Lifetime Warranty

Custom Options:

- Low-E Glass
- Low-E Glass + Argon Gas
- Ultra Low-E Glass + Argon Gas
- Charcoal aluminum mesh screen
- 5/8" or 3/4" flat, 5/8" or 1" contoured, 1 1/8" Simulated Divided Lite

Product Performance:

AAMA 101 Results:

Window Size	AAMA Rating (psf)	Air (cfm/ft ²)	Water (psf)
52" x 36" (X Fin)	C45	0.07	9.19
96" x 36" (XX CHS Fin)	C35	0.01	8.35
108" x 36" (XXX CHS Fin)	C50	0.04	9.19
48" x 96" (O/X w/ 3'0" High Sash CHS)	C45	0.03	9.19

Acoustic Results:

Glazing	STC
3/32" – 9/16" Airspace – 3/32"	25
1/8" – 1/2" Airspace – 1/8"	28

Product Dimensions:

Vinyl Wall Thickness:	0.075"
Glass Thickness:	0.750"
Jamb Depth:	3.250"
Nail Fin Setback:	2.1875"

Rough Opening:

Window Width + 1/2"
Window Height + 1/2"

Single Vent Awning Size Restrictions:

	Min:	Max:
Width	19"	48"
Height	14"	36"



755 Awning Window

Egress Formulas:

Product does not meet egress requirements.

Awning Screen Formulas:

Window Width – 4.375"

Window Height – 4.3125"

Cross Sections:

