



## SERIES 8050

### VINYL SIDE-LOAD SINGLE HUNG WINDOW

- + Removable bottom sash
- + Industry leading .01 cfm/ft. air infiltration performance
- + Multi-cavity vinyl lineals improve thermal performance and enhance sound absorbency
- + Insulating glass provides energy saving thermal efficiency
- + Fusion welded frame and sash minimizes air and water infiltration and enhances overall durability
- + Sweep lock helps provide a weather-tight seal and added security
- + Removable operable sash includes full-length interlock and bottom weather reflector
- + Dual screw boss, metal reinforced meeting rail provides added strength
- + Custom sized to the nearest 1/8"
- + Dual weather-stripping helps block air and water infiltration, keeping harsh elements outside and energy saving comfort inside
- + Versatile half-screen\* installed from the inside or outside
- + Sloped sill reduces air infiltration and accommodates easy water run-off
- + Built-in accessory channels accommodate multiple installation options
- + Transferable, limited lifetime warranty
- + DP-50 Rating (window size tested 36" x 96")
- + Jamb depth: 2.625"

### CUSTOM Options

- + Low-E Glass
- + Low-E Glass + Argon Gas
- + Ultra Low-E Glass + Argon Gas
- + 5/8" or 3/4" flat, 5/8" or 1" contoured, 5/8" contoured valance grids available
- + Factory mulling of twins, triples and architectural shapes
- + Custom sizes available
- + Safety latch for sash restriction (field applied)

### + COLOR OPTIONS\*\*



Scan to experience our website.



ENERGY STAR compliance available in all series. Verify product specifics before ordering.

Note: Manufacturer reserves the right to substitute components as necessary for continued product improvement.

\* Screens are not meant to restrain a child from falling through an open window.

\*\* Printing process may affect color shown. Please refer to actual window sample when selecting colors.