

## 8100 Single Hung Window

### Features:

- Bottom sash tilts in for easy cleaning
- Insulated glass panels with optimum thermal air space featuring a warm-edge spacer system
- Double sash locks provide extra security (2 locks standard at 27 1/4" or wider)
- Block & tackle balance system keeps lower sash stationary when opened to any position
- Factory applied wrap-around foam enhances thermal efficiency around the frame's exterior
- Fusion-welded frame and sash corners ensure frame durability
- Sloped sill accommodates easy water run-off
- Factory-installed half screen standard
- Jamb depth: 2.625"
- Transferable limited lifetime warranty

### Custom Options:

- Low-E Glass
- Low-E Glass with Argon Gas
- Ultra Low-E Glass with Argon Gas
- Obscure glass
- Double strength glass
- Optional 5/8" or 1" contoured grid; 5/8" or 3/4" flat grid, 5/8" contoured valance available
- Custom sizes cut on 1/8" width and height
- Factory mulling of twins and triples
- Lifetime glass breakage warranty

### Product Performance:

AAMA 101 Results:

Window Size	AAMA Rating (psf)	Air (cfm/ft <sup>2</sup> )	Water (psf)
48" x 78" (O/X)	R-PG25	0.26	7.52
36" x 74" (O/X)	R-PG50	0.26	7.52
109" x 74" (O/X – O/X – X/X SH HP Muller Triple)	DP50	0.17	7.52

### Product Dimensions:

Vinyl Wall Thickness:	0.070"
Typ. Glass Thickness:	0.750"
Jamb Depth:	2.625"
Mullion Adder:	
Standard:	0.500"
High Performance:	0.500"

### Rough Opening:

Window Width + 1/4"  
Window Height + 1/4"

### Size Restrictions:

	Min:	Max:
Width	16 7/8"	51 3/4"
Height	23 1/2"	89 3/4"

(Max. United Inches 132")



## 8100 Single Hung Window

### Egress Formulas:

Egress Width  $\geq 20"$  and Egress Height  $\geq 24"$  and Egress Area  $\geq 5.7 \text{ ft}^2$  required to meet egress.

Egress Width Formula = Window Width - 5.3125"

Egress Height Formula = (Window Height/2) - 4.5"



Egress Area Formula = (Egress Width x Egress Height)/144

### Screen Formulas:

Window Width - 4.3125" (1/2 Screen)


(Window Height/2) - 1.3750" (1/2 Screen)

### Cross Sections:



### Standard Mullion Assembly:

(not structurally rated)



### High Performance Mullion Assembly:

