



SERIES 8100 SLIDING WINDOW

- + **Insulated glass panels** with optimum thermal air space featuring a warm-edge spacer system
- + **Aluminum-reinforced** lock and meeting rails enhance structural integrity
- + **Tandem rollers** ride easily along friction free glide channel
- + **Integrated glide rail** for easy sash opening and closing
- + **Available in** ¼ - ½ - ¼ or ⅓ - ⅓ - ⅓ configurations
- + **XO or OX 2-lite styles available**
- + **Double sash locks** provide extra security (2 locks standard at 27 ¼" or higher)
- + **Beveled exterior frame** makes a stylish design statement
- + **Factory applied wrap-around foam** enhances thermal efficiency around the frame's exterior
- + **Fusion-welded frame** and sash corners ensure frame durability
- + **Sloped sill** accommodates easy water run-off
- + **Factory-installed half screen standard***
- + **Head expander and sill angle** are included
- + **Jamb depth: 2.75"**
- + **Transferable limited lifetime warranty**



2-lite sliding window



3-lite sliding window

CUSTOM Options

- + **Low-E Glass**
- + **Low-E Glass + Argon Gas**
- + **Ultra Low-E Glass + Argon Gas**
- + **Obscure glass**
- + **Double strength glass**
- + **Optional 5/8" or 1" contoured, 5/8" or 3/4" flat grids available**
- + **Custom sizes cut on 1/8" width and height**
- + **Factory mulling of twins and triples**
- + **Charcoal aluminum mesh screen***
- + **Lifetime glass breakage warranty**

+ COLOR OPTIONS**



Scan to experience our website.



ENERGY STAR compliance available in all series. Verify product specifics before ordering.

Note: Manufacturer reserves the right to substitute components as necessary for continued product improvement.

* Screens are not meant to restrain a child from falling through an open window.

** Printing process may affect color shown. Please refer to actual window sample when selecting colors.