

SERIES 8900 DOUBLE HUNG

- + Series 8900 2- and 3-lite sliders and picture windows are available
- + Exclusive InsulKor™ polyurethane fiberglass-enriched sash reinforcement for superior thermal and structural performance
- + 3/4" constant force coil balance offers incredibly easy sash mobility
- + Fusion-welded sashes and frame add strength and boost insulation
- + Low-E glass with insulating argon gas yields outstanding thermal efficiency
- + DP-60 rating (window size tested 36" x 74")
- + Beveled mainframe offers a stylish exterior appearance
- + Dual push-button night latches position sashes for optimal ventilation
- + Integrated slim-line lift rail allows you to easily operate sash
- + 4 1/4" frame thickness enhances appearance as well as structural integrity
- + External accessory groove accommodates nail fin option
- + Full screen is standard and removable from the inside*
- + Dual low profile, positive-action cam locks increase security (2 locks standard at 27 1/4" width or wider)
- + Full interlocking lock and meeting rail
- + Full vinyl sash dam on sill and high-performance weather stripping protect against air infiltration
- + 3.25" jamb depth for ideal window sizing
- + Transferable limited lifetime warranty
- + Lifetime glass breakage warranty



CUSTOM Options

- + Low-E Glass
- + Ultra Low-E Glass + Argon Gas
- + Triple-pane, R-5 compliant glass panels
- + InsulKor™ multi-cavity foam-filled frame injections
- + Nail fin accessory for use in remodeling or new construction applications
- + 1 1/8" simulated divided lite (SDL) grid
- + 5/8" or 1" contoured, 5/8" or 3/4" flat, 5/8" contoured valance grids available
- + Obscure or double-strength glass
- + Charcoal aluminum, Clear View and heavy duty screens*

INSULKOR™
TECHNOLOGY




Scan to watch a video about our Series 8900.

+ COLOR OPTIONS**



+ LOCK OPTIONS**



ENERGY STAR compliance available in all series. Verify product specifics before ordering.

Note: Manufacturer reserves the right to substitute components as necessary for continued product improvement.
* Screens are not meant to restrain a child from falling through an open window.
** Printing process may affect color shown. Please refer to actual window sample when selecting colors.
*** Grid offering limited to 5/8" contoured or SDL on exterior painted windows. Only use mild, water based household cleaner on painted product and rinse immediately with water. See full cleaning instructions for details.

